

# 118-A series

**BOX HEADER 2.54mm(0.100" )**

| Position | A     | B     | C     | Position | A     | B     | C     |
|----------|-------|-------|-------|----------|-------|-------|-------|
| 10       | 20.30 | 18.10 | 10.16 | 30       | 45.70 | 43.50 | 35.56 |
| 12       | 22.84 | 20.64 | 12.70 | 34       | 50.78 | 48.58 | 40.64 |
| 14       | 25.38 | 23.18 | 15.24 | 40       | 58.40 | 56.20 | 48.26 |
| 16       | 27.92 | 25.72 | 17.78 | 50       | 71.10 | 68.90 | 60.96 |
| 20       | 33.00 | 30.80 | 22.86 | 60       | 83.80 | 81.60 | 73.66 |
| 26       | 40.62 | 38.42 | 30.48 | 64       | 88.88 | 86.68 | 78.74 |


## Specifications:

Contact Resistance: 30mΩ max.at DC 100 mA  
Insulator Resistance: 1000MΩ min.at DC 500V  
Current Rating: 1AMP

## Dielectric Withstanding

Voltage: AC 500V For 1 minute  
Operating Temperature: -55° C +105° C  
Contact: Brass  
Housing: PBT &30% Glass Fiber(UL 94V-0)

### [STRAIGHT]



### [RIGHT ANGLE]

